313258

FTR4FG9/B

Freestanding gas griddle with brushed, chrome-plated, ribbed plate on open cabinet

- Gas griddle on an open cabinet (40 cm) with a brushed chrome-plated, ribbed cooking plate to cook a variety of products: from meat to fish and vegetables.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances the grilling of various products
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- Heating through 1 2-branch steel burner.
- Operating thermostatic valve with temperature ranging between 150°C and 300°C.
- Safety thermostat.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Sloped Inclined cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

TECHNICAL DATA

TOTAL POWER	8 kW	GAS POWER	8 kW
TEMPERATURE RANGE	60÷300 °C	NATURAL GAS CONSUMPTION	0,84 m³/h
CABINET DIMENSIONS	33X76,1X39,5 cm	COOKING SURFACE	34,9X69,8 cm
PLATE TYPE	BRUSHED CHROME-PLATED - RIBBED	HEATING ZONES	n° 1
CE GAS CERTIFICATE NUMBER	CE-0085BO0093	GAS CONNECTION DIAMETER	1/2"G EN10226-1
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
WIDTH	40 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	100 cm
PACKAGE DEPTH	46 cm	PACKAGE HEIGHT	115 cm
NET WEIGHT	67 kg	GROSS WEIGHT	82 kg
VOLUME	0,53 m³		

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - REPLACEMENT BLADE KIT (10 PIECES)
120598	SCRAPER - REPLACEMENT BLADE KIT FOR RIBBED PLATE (10 PIECES)
319002	STAINLESS STEEL RIGHT/LEFT DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
319055	SIDE HEAT PROTECTION FOR GRIDDLES
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

INSTALLATION DIAGRAMS



Fig.1 | Abb.1 | рис.1 | | الصورة رق ١ - 5415.618.00