313268

PCH8SG9

4-burner hermetic gas boiling top Super with cast iron grids



- 4-burner gas boiling top (80 cm), SUPER version.
- High-efficiency cast-iron burners hermetically fixed to the top and highly durable brass flame spreaders with single ring (6kW and 10kW) and double ring (11kW).
- Deep drawn worktop to prevent overflows and with rounded corners for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grids to resist acids, alkalis and flames.
- Setup for installing a water tap.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

TECHNICAL DATA

TOTAL POWER	37 kW	GAS POWER	37 kW
OPEN BURNER POWER	1X6+2X10+1X11 n°- kW	BOILING TOP POWER	37 kW
NATURAL GAS CONSUMPTION	3,92 m³/h	NUMBER OF BURNERS	n° 4
BOILING PAN SUPPORT	RAAF ENAMELLED CAST IRON	CE GAS CERTIFICATE NUMBER	CE-0085BQ0326
GAS CONNECTION DIAMETER	3/4"G EN10226-1	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	28 cm
PACKAGE WIDTH	86,0 cm	PACKAGE DEPTH	101 cm
PACKAGE HEIGHT	55 cm	NET WEIGHT	75,8 kg
GROSS WEIGHT	86 kg	VOLUME	0,48 m³

ACCESSORIES

319067	10KW HERMETIC FLAME SPREADER
319068	HERMETIC FLAME SPREADER (5 - 6 - 7,5 KW)
399516	ADJUSTABLE WATER TAP
399538	PAN SUPPORT REDUCER
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

INSTALLATION DIAGRAMS



Fig.1 | Abb.1 | рис.1 | | الصورة رق ١ - 5415.618.00