313287

PFH12SGG9

6-burner hermetic gas boiling top Super with cast iron grids on GN2/1 gas static oven with 1 grid



- 6-burner gas cooker on a GN 2/1 gas static oven and cabinet with door, total width 120 cm, SUPER version.
- High-efficiency cast-iron burners hermetically fixed to the top and highly durable brass flame spreaders with single ring (6kW and 10kW) and double ring (11kW).
- Deep drawn worktop to prevent overflows and with rounded corners for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grids to resist acids, alkalis and flames.
- Setup for installing a water tap.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

  >> GN 2/1 GAS STATIC OVEN
  >> AISI 304 stainless steel oven door.
  >> Stainless steel cooking chamber and long-lasting steel mesh and glass fibre gasket resistant to high temperatures.
  >> Equipped with thermostatic valve, 150-290°C adjustment.
  >> Pilot burner ignition with a thermocouple through a piezoelectric device.
  >> Removable stainless steel side tray racks.
  >> 1 grid included.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

TECHNICAL DATA

TOTAL POWER	61 kW	GAS POWER	61 kW
OVEN POWER	7 kW	OPEN BURNER POWER	6X2 + 10X2 + 11X2 n°- kW
BOILING TOP POWER	54 kW	TRAY CAPACITY	n° 4XGN2/1
NATURAL GAS CONSUMPTION	6,46 m³/h	COOKING CHAMBER DIMENSIONS	57,5X65X30 cm
OVEN DIMENSIONS	GN2/1	CABINET DIMENSIONS	33X76,1X39,5 cm
GUIDES	n° 4	NUMBER OF BURNERS	n° 6
VERTICAL DISTANCE BETWEEN TRAYS	6 cm	OVEN TEMPERATURE RANGE	150÷290 °C
BOILING PAN SUPPORT	RAAF ENAMELLED CAST IRON	OVEN TYPE	STATIC
CE GAS CERTIFICATE NUMBER	CE-0085BQ0326	GAS CONNECTION DIAMETER	3/4"G EN10226-1
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
WIDTH	120 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	124 cm
PACKAGE DEPTH	99 cm	PACKAGE HEIGHT	116,0 cm
NET WEIGHT	190 kg	GROSS WEIGHT	215 kg
VOLUME	1,42 m³		

ACCESSORIES

220590	EXTRA OVEN GRID GN2/1 (53X63CM)
319011	REAR COVERING PANEL FOR CABINET (L=120CM)
319067	10KW HERMETIC FLAME SPREADER
319068	HERMETIC FLAME SPREADER (5 - 6 - 7,5 KW)
399516	ADJUSTABLE WATER TAP
399530	SIDE COVERING PANEL FOR A 1-MODULE CABINET
399538	PAN SUPPORT REDUCER
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

INSTALLATION DIAGRAMS



Fig.1 | Abb.1 | рис.1 | | الصورة رق ١ - 5415.618.00