

316128

PIW4FE9**Freestanding wok induction boiling top on open cabinet**



- Freestanding wok induction boiling top (40 cm) on an open cabinet.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Glass ceramic top (Ø 30 and 6 mm thick) hermetically sealed to the top for maximum hygiene and ease of cleaning.
- 5 kW single area.
- Power regulator 0-6-infinite.
- Increased heating speed compared to other wok types.
- Heating is enabled only when in contact with the pan, saving energy and reducing overheating.
- Front air filter drawer easily accessible for cleaning and replacement.
- LED light for detecting pans and signalling operation and errors.
- To optimise efficiency, use high-quality induction wok pans.
- Technical compartment for easy connection to the electrical network.
- Avoid placing above ovens or refrigerated bases.



TECHNICAL DATA

TOTAL POWER	5 kW	ELECTRIC POWER	5 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
COOKING ZONE POWER	1X5 n°- kW	CABINET DIMENSIONS	33X76,1X39,5 cm
NUMBER OF COOKING ZONES	n° 1	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	IPX RATING	4
WIDTH	40 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	101 cm
PACKAGE DEPTH	46,0 cm	PACKAGE HEIGHT	115,0 cm
NET WEIGHT	43 kg	GROSS WEIGHT	55,5 kg
VOLUME	0,53 m³		

ACCESSORIES

319002	STAINLESS STEEL RIGHT/LEFT DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
399530	SIDE COVERING PANEL FOR A 1-MODULE CABINET
399569	ADJUSTABLE WATER TAP FOR KITCHENS WITH A FLUE
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION DIAGRAMS




Fig.1 | Abb.1 | рис.1 - 5415.561.00