

716023

PP8E7**Electric solid boiling top (top version)**



- Electric solid top (80 cm) with 4 independent zones areas.
- Electric solid tops and cookers are suitable for indirect cooking only.
- Overflow-proof worktop with raised and welded edges.
- Non-deformable, molybdenum steel plate (15 mm thick) with prolonged heat retention properties.
- Ultra-fast radiant heating elements secured under the 2.0 kW plate for each independent area.
- Ultra-rapid infrared heating elements secured under the plate with a power of 2.0 kW for each independent zone.
- Maximum temperature of 470°C.
- Energy regulator 0-6-infinite.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each zone.
- Safety thermostat.
- Lights warning when the heating areas are active.
- Setup for installing a water tap.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to facilitate connection to the electrical network.



TECHNICAL DATA

TOTAL POWER	8 kW	ELECTRIC POWER	8 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
BOILING TOP POWER	8 kW	COOKING ZONE POWER	4X2 n°- kW
ELECTRIC PLATE DIMENSIONS	76,3X58 cm	NUMBER OF COOKING ZONES	n° 4
PLATE TEMPERATURE RANGE	MAX 450 °C	PLATE TYPE	IRON AND MOLYBDENUM
HEATING ZONES	n° 4	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	IPX RATING	4
WIDTH	80 cm	DEPTH	70 cm
HEIGHT	28 cm	PACKAGE WIDTH	88 cm
PACKAGE DEPTH	81,0 cm	PACKAGE HEIGHT	56,0 cm
NET WEIGHT	70,5 kg	GROSS WEIGHT	80,5 kg
VOLUME	0,40 m³		

ACCESSORIES

799506	PAIR OF CLOSING ELEMENTS (L=70CM)
--------	-----------------------------------

INSTALLATION DIAGRAMS




Fig.1 | Abb.1 | pvc.1 - 5415.657.00