954650

EOM06TSL

Tecnocombi NEXT electric combi steamer with 6 trays GN1/1 touch screen, programmable recipes, core probe and automatic washing, direct steam

- 6-tray GN 1/1 electric combi steamer, Touch control screen, with direct steam.
- Deep drawn and hermetically welded cooking chamber.
- Cooking chamber lighting through LEDs in the door.
- Cooking chamber made of AISI 304 stainless steel (1 mm thick) featuring rounded corners to prevent dirt buildups. The polished steel finish improves heat refraction, reduces steel roughness, and prevents corrosion from chemicals, allowing easy removal of food residues.
- AISI 304 watertight door with high-performance and easily replaceable gasket and 2 glass panes: the outer pane is 4 mm thick and the inner pane is 6 mm thick with a thermal reflective treatment for enhanced energy efficiency. Air tunnel in the door for operator safety.
- Anti-slip and anti-fingerprint handle with right/left opening.
- The interface is as user-friendly as a smartphone, thanks to a 7-inch capacitive touch display.
- The cooking parameters are easily visible at a glance, thanks to the automatic distance display mode.
- The 8 cooking cycles help save energy and obtain excellent results.
- The professional fans are governed by an inverter, work with 4 speeds and stop instantly when rotation is reversed and the door is opened.
- In the mixed cycle you can manage up to 19 humidity levels at 5% intervals from 0% to 90%.
- Programmable steam puff up to 20 seconds, enhancing humidity levels in the cooking chamber during convection mode.
- Up to 300 cooking programs, including both uploaded and chef-created ones.
- Multifood technology for cooking several foods simultaneously.
- Automatic self-cleaning including 4 cycles, with the longest lasting only 62 minutes.
- Multipoint core probe with 4 detection points included.
- Cloud platform for controlling recipes and ovens easily.
- HACCP and consumption data recording.

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

TECHNICAL DATA

TOTAL POWER	8,25 kW	ELECTRIC POWER	8,25 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
MOTOR FAN ELECTRIC POWER	0,25 kW	CONVECTION UNIT POWER	8 kW
TRAY CAPACITY	n° 6XGN1/1	MAXIMUM FOOD LOAD	30 Kg
COOKING CHAMBER DIMENSIONS	59X38X45 cm	GUIDES	n° 6
VERTICAL DISTANCE BETWEEN TRAYS	6,5 cm	THERMAL INSULATION THICKNESS	35 mm
STEAM CYCLE TEMPERATURE	50÷120 °C	MIXED CYCLE TEMPERATURE	50÷250 °C
CONVECTION CYCLE TEMPERATURE	50÷265 °C	TIMER	0-540 min
OVEN TYPE	DIGITAL - GN1/1 TRAY	FAN SPEED	4
WATER CONNECTION POSITION	4CM	WATER DRAIN POSITION	4CM
WATER CONNECTION DIAMETER	3/4"	DRAIN DIAMETER	1,9685"
FOOT HEIGHT	65 mm	FOOT ADJUSTMENT	65/75 mm
IPX RATING	4	WIDTH	86 cm
DEPTH	72 cm	HEIGHT	74 cm
PACKAGE WIDTH	93 cm	PACKAGE DEPTH	87 cm
PACKAGE HEIGHT	100 cm	NET WEIGHT	90 kg
GROSS WEIGHT	104 kg	VOLUME	0,80 m³

ACCESSORIES

091910	GN1/1 STAINLESS STEEL BAKING GRID FOR POULTRY
091946	STAINLESS STEEL MESH BASKET FOR PRE-FRIED FOOD
091947	TEFLON-COATED ALUMINIUM SPECIAL GRID FOR VEGETABLES
091949	STAINLESS STEEL BAKING GRID FOR SKEWERS
091950	ALUMINIUM TEFLON-COATED SPECIAL GRID FOR MEAT AND FISH
091951	ALUMINIUM TEFLON COATED TRAY FOR EGGS AND OMELETTES
091952	ALUMINIUM SMOOTH TEFLON-COATED TRAY H=20MM
091953	ALUMINIUM SMOOTH TEFLON-COATED TRAY H=40MM
091954	ALUMINIUM SMOOTH TEFLON-COATED TRAY H 65MM
9032	GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=20MM
9033	GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=40MM
9034	GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=65MM
9055	GN1/1 STAINLESS STEEL BAKING GRID
9056	GN1/1 STAINLESS STEEL PERFORATED BAKING TRAY H=20MM
9057	GN1/1 STAINLESS STEEL PERFORATED BAKING TRAY H=40MM
9058	GN1/1 STAINLESS STEEL PERFORATED BAKING TRAY H=65MM
9059	GN1/1 ENAMELLED BACKING TRAY H=20MM
9060	GN1/1 ENAMELLED BACKING TRAY H=40MM
9061	GN1/1 ENAMELLED BACKING TRAY H=65MM
951912	EXTERNAL SPRAY GUN
951915	ALKALINE DETERGENT TANK (10LT) FOR OVENS
951917	ALUMINIUM TRAY WITH HEAT RETENTION FOR PIZZA (GN1/1)
951933	ALUMINIUM SMOOTH TEFLON COATED TRAY WITH HEAT RETENTION
951934	ALUMINIUM RIBBED TEFLON COATED TRAY WITH HEAT RETENTION
951938	CLOSED CABINET WITH SIDE RUNNERS AND DETERGENT TANK SUPPORT FOR GN1/1 OVENS - 7 TRAYS CROSSWISE
951953	TEFLON COATED ALUMINIUM TRAY GN1/1
951954	PERFORATED TEFLON COATED ALUMINIUM TRAY GN1/1
951961	PIPING KIT FOR WATER INLET AND OUTLET
951967	GN TRAY RACK KIT FOR OVENS BASE (6/10 TRAYS)
951972	COVERING PANEL FOR TECNOCOMBI OVENS WITH EXHAUST HOOD ON BASE, CABINET, HOT CABINET OR HUMIFIED CABINET
951974	BASE FOR 6 AND 10 GN1/1 TRAY TECNOCOMBI OVENS
951976	BASE WITH SIDE RUNNERS FOR 6 AND 10 GN1/1 TRAYS TECNOCOMBI OVENS
951981	STACKING ELEMENT FOR 6 AND 10 GN1/1 TRAY TECNOCOMBI OVENS ON 5-TRAY BLAST FREEZERS
951983	WHEELS KIT FOR OVENS BASE
951991	BASE FOR TECNOCOMBI ELECTRIC OVENS ON 5 TRAYS BLAST CHILLER.
951992	CONDENSATING EXTRACTOR HOOD FOR 6 GN1/1AND 10 GN1/1 TECNOCOMBI, 230V, 50/60HZ,0.25 KW MOTOR
951993	STACKING KIT FOR 6+10 TRAYS TECNOCOMBI ELECTRIC OVENS
951994	STACKING KIT FOR 6+6 TRAYS TECNOCOMBI ELECTRIC OVENS
951995	

TECNOINOX Srl reserves the right to make changes at any time without prior notice.

tecnoinox.it

INSTALLATION DIAGRAMS



TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it