962353

D series Tecnodual XTRA gas combi steamer with 10 trays (GN1/1 or 600x400mm) electronic control, programmable recipes and direct steam

- 10-tray GN 1/1 or 60x40 cm gas digital combi steamer with direct steam and atmospheric burners.
- Cooking chamber lighting through LEDs in the door.
- Deep drawn and hermetically welded cooking chamber.
- Cooking chamber made of AISI 304 stainless steel (1 mm thick) featuring rounded corners to prevent dirt buildups. The polished steel finish improves heat refraction, reduces steel roughness, and prevents corrosion from chemicals, allowing easy removal of food residues.
- AISI 304 watertight door with high-performance and easily replaceable gasket and 2 glass panes: the outer pane is 4 mm thick and the inner pane is 6 mm thick with a thermal reflective treatment for enhanced energy efficiency. Air tunnel in the door for operator safety.
- Anti-slip and anti-fingerprint handle with right/left opening.
- The capacitive touch buttons and push & scroll dial speed up the selection and confirmation procedures.
  The control panels are equipped with:
  - two alphanumeric displays: one for temperature control and one for time or the temperature detected by the core probe;
  - a high-visibility colour LCD-TFT display, ensuring optimal visualisation of recipes and 8 energy-efficient cooking cycles for excellent end results.
- The professional fans are governed by an inverter, work with 4 speeds and stop instantly when rotation is reversed and the door is opened.
- In the mixed cycle you can manage up to 19 humidity levels at 5% intervals from 0% to 90%.
- The play button lights up in different colours to show the status of the oven.
- Programmable steam puff up to 20 seconds, enhancing humidity levels in the cooking chamber during convection mode.
- Up to 300 cooking programs, including both uploaded and chef-created ones.
- Cloud platform for controlling recipes and ovens easily.

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

TECHNICAL DATA

TOTAL POWER	19,5 kW	GAS POWER	19 kW
ELECTRIC POWER	0,5 kW	FREQUENCY	50/60 Hz
VOLTAGE	220-240 ~ V	MOTOR FAN ELECTRIC POWER	0,5 kW
NOMINAL THERMAL POWER	19 kW	TRAY CAPACITY	n° 10XGN1/1O10X(600X400
NATURAL GAS CONSUMPTION	2,01 m³/h	COOKING CHAMBER DIMENSIONS	68X45X73 cm
GUIDES	n° 10	VERTICAL DISTANCE BETWEEN TRAYS	6,5 cm
THERMAL INSULATION THICKNESS	35 mm	STEAM CYCLE TEMPERATURE	50÷120 °C
MIXED CYCLE TEMPERATURE	50÷250 °C	CONVECTION CYCLE TEMPERATURE	50÷265 °C
TIMER	0-540 min	OVEN TYPE	DIGITAL - GN1/1 TRAY OR 400 X 600 MM
FAN SPEED	4	CE GAS CERTIFICATE NUMBER	CE-0085CP0593
WATER CONNECTION POSITION	4CM	WATER DRAIN POSITION	4CM
GAS CONNECTION DIAMETER	1/2"G EN10226-1	WATER CONNECTION DIAMETER	3/4"
DRAIN DIAMETER	1,9685"	FOOT HEIGHT	65 mm
FOOT ADJUSTMENT	65/75 mm	IPX RATING	3
WIDTH	95 cm	DEPTH	80 cm
HEIGHT	102 cm	PACKAGE WIDTH	101 cm
PACKAGE DEPTH	93 cm	PACKAGE HEIGHT	127 cm
NET WEIGHT	128 kg	GROSS WEIGHT	154,5 kg
VOLUME	1,19 m³		

ACCESSORIES

091910	GN1/1 STAINLESS STEEL BAKING GRID FOR POULTRY
091946	STAINLESS STEEL MESH BASKET FOR PRE-FRIED FOOD
091947	TEFLON-COATED ALUMINIUM SPECIAL GRID FOR VEGETABLES
091949	STAINLESS STEEL BAKING GRID FOR SKEWERS
091950	ALUMINIUM TEFLON-COATED SPECIAL GRID FOR MEAT AND FISH
091951	ALUMINIUM TEFLON COATED TRAY FOR EGGS AND OMELETTES
091952	ALUMINIUM SMOOTH TEFLON-COATED TRAY H=20MM
091953	ALUMINIUM SMOOTH TEFLON-COATED TRAY H=40MM
091954	ALUMINIUM SMOOTH TEFLON-COATED TRAY H 65MM
9032	GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=20MM
9033	GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=40MM
9034	GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=65MM
9037	CHROME-PLATED GRID (600X400MM)
9041	SMOOTH ALUMINIUM TRAY 600X400 H=20MM
9045	PERFORATED ALUMINIUM TRAY 600X400 H=65MM
9046	ALUMINIUM BAGUETTES BAKING TRAY
9055	GN1/1 STAINLESS STEEL BAKING GRID
9056	GN1/1 STAINLESS STEEL PERFORATED BAKING TRAY H=20MM
9057	GN1/1 STAINLESS STEEL PERFORATED BAKING TRAY H=40MM
9058	GN1/1 STAINLESS STEEL PERFORATED BAKING TRAY H=65MM
9059	GN1/1 ENAMELLED BACKING TRAY H=20MM
9060	GN1/1 ENAMELLED BACKING TRAY H=40MM
9061	GN1/1 ENAMELLED BACKING TRAY H=65MM
951912	EXTERNAL SPRAY GUN
951917	ALUMINIUM TRAY WITH HEAT RETENTION FOR PIZZA (GN1/1)
951933	ALUMINIUM SMOOTH TEFLON COATED TRAY WITH HEAT RETENTION
951934	ALUMINIUM RIBBED TEFLON COATED TRAY WITH HEAT RETENTION
951935	DRAUGHT DIVERTER FOR TECNOCOMBI GAS OVENS 6-10 TRAYS
951953	TEFLON COATED ALUMINIUM TRAY GN1/1
951954	PERFORATED TEFLON COATED ALUMINIUM TRAY GN1/1
951961	PIPING KIT FOR WATER INLET AND OUTLET
951983	WHEELS KIT FOR OVENS BASE
961910	ALUMINIUM TRAY WITH HEAT RETENTION FOR PIZZA (600X400 MM)
961937	CLOSED CABINET WITH SIDE RUNNERS AND DETERGENT TANK SUPPORT FOR PASTRY OVENS
961950	TEFLON COATED ALUMINIUM TRAY (600X400MM)
961951	TEFLON COATED ALUMINIUM PERFORATED TRAY (600X400MM)
961963	DUAL TRAY RACK KIT FOR OVEN BASE
961979	CONDENSING EXTRACTOR HOOD FOR 5 AND 8 TRAYS TECNOBAKE OR 6 AND 10 TRAYS TECNODUAL OVENS, 230V, 50/60HZ, 0.25KW MOTOR
961980	BASE WITH SIDE RUNNERS FOR 6 AND 10 GN1/1 TRAYS TECNODUAL OVENS
961981	BASE FOR TECNOBAKE AND TECNODUAL OVENS ON A 5 TRAYS BLAST FREEZER
961982	COVERING PANEL FOR TECNOCOMBI OVENS WITH HOOD ON BASE, CUPBOARD, HOT CUPBOARD OR HUMIFIED CUPBOARD
961985	BASE WITH SIDE RUNNERS FOR TECNODUAL 6 AND 10 TRAY OVENS / TECNOBAKE 5 OR 8 TRAY OVENS

TECNOINOX Srl reserves the right to make changes at any time without prior notice.
tecnoinox.it

INSTALLATION DIAGRAMS



TECNOINOX Srl reserves the right to make changes at any time without prior notice.

tecnoinox.it